Key **Features**

- Lifelike True Beauty: International color standard Pantone validated and 100% sRGB wide color gamut
- Precise Color: ColorPro Verified with prefactory calibration for overwhelmed Delta E <
 2 color accuracy
- Multimedia Devices: Support USB-C with 60W high-speed charging, plus HDMI 1.4, DisplayPort 1.2a, USB 3.2
- Unlimited Flexibility: Auto Pivot &
 Ergonomic Stand with tilt, swivel, pivot, and
 height adjustments
- The Visible Difference: 2K QHD(2560* 1440) resolution IPS panel with 27" frameless design



Product **Description**

Designed with creative professionals in mind, the ViewSonic VP2756-2k delivers stunning true-to-life colors on screen. Pantone validated 100% sRGB coverage provides precise color reproduction, ensuring your work looks how it should, every time. A USB-C port that easily connects with your devices for easy charging and data transfer. Ergonomic engineering gives you the flexibility to do more without injury, while Auto Pivot lets shift between horizontal and vertical orientations effortlessly, letting your work be viewed how it's supposed to be.

Visit Us

www.viewsonic.com

DISPLAY		INPUT SIGNAL	
Display Size (in.):	27	Frequency Horizontal:	15 ~ 130KHz
Viewable Area (in.):	27	Frequency Vertical:	24 ~ 75Hz
Panel Type:	IPS Technology	VIDEO INPUT	
Resolution:	2560 x 1440		TMDS - HDMI (v1.4), PCI-E -
Resolution Type:	QHD (Quad HD)	Digital Sync:	DisplayPort (v1.2), Micro-Packet - Type C
Static Contrast Ratio:	1,000:1 (typ)	ERGONOMICS	.,,,,
Dynamic Contrast Ratio:	20M:1	Height Adjust (mm):	130
•	LED	Swivel:	120°
Light Source:		Tilt (Forward/Back):	-5° / 21°
Brightness: Colors:	350 cd/m² (typ)	Pivot (Right/Left):	90° / 90°
	16.7M	WEIGHT (IMPERIAL)	00 / 00
Color Space Support:	8 bit true	Net (lbs):	15.1
Aspect Ratio:	16:9	Net Without Stand (lbs):	9.8
Response Time (Typical GTG):	5ms	Gross (lbs):	21
Response Time (GTG w/OD):	5ms	WEIGHT (METRIC)	21
Viewing Angles:	178º horizontal, 178º vertical	Net (kg):	6.9
Backlight Life (Hours):	30000 Hrs (Min)	Net Without Stand (kg):	4.4
Curvature:	Flat	, ,,	
Refresh Rate (Hz):	60	Gross (kg):	9.5 VUVD)
Blue Light Filter:	Yes	DIMENSIONS (IMPERIAL) (W.	
Flicker-Free:	Yes	Packaging (in.):	29.1 x 18.3 x 8.9
	Adobe RGB: 81% size / 78%	Physical (in.):	24.1 x 16.15~21.27 x 8.5
	coverage (Typ) DCI-P3: 81% size / 81% coverage (Typ) EBU: 108% size	Physical Without Stand (in.):	24.1 x 14.3 x 2.1
Color Gamut:	/ 99% coverage (Typ) REC709: 110% size / 100% coverage (Typ) SMPTE-C: 118% size / 100% coverage (Typ) NTSC: 78% size (Typ) sRGB: 110% size / 100% coverage (Typ)	DIMENSIONS (METRIC) (WXI	· ·
		Packaging (mm):	740 x 465 x 225
		Physical (mm):	613 x 410.31~540.31 x 215
Pixel Size:	0.233 mm (H) x 0.233 mm (V)	Physical Without Stand (mm):	613 x 363 x 53
Surface Treatment:	Anti-Glare, Hard Coating (3H)	GENERAL	
COMPATIBILITY			cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico
PC Resolution (max):	2560x1440	Regulations:	Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC,
Mac® Resolution (max):	2560x1440		UkrSEPRO, UKCA, BSMI
PC Operating System:	Windows 10/11 certified; macOS tested	PACKAGE CONTENTS:	VP2756-2K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male- Male) x1, USB Type-C Cable (Male- Male) x1, USB A/B Cable (v3.2; Male- Male) x1, Quick Start Guide x1
Mac® Resolution (min):	2560x1440		
CONNECTOR			Please dispose of in accordance with
USB 3.2 Type A Down Stream:	2	Recycle/Disposal:	local, state or federal laws.
USB 3.2 Type B Up Stream:	1	Warranty:	*Warranty offered may differ from market to market
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1	Power Management:	Energy Star standards, EPEAT
HDMI 1.4:	1		
DisplayPort:	1		
Power in:	3-pin Socket (IEC C14 / CEE22)		
AUDIO	0M # 0		
Internal Speakers:	2Watts x2		
POWER	16 EW		
Eco Mode (Conserve):	16.5W		
Eco Mode (optimized):	19.3W		
Consumption (typical):	22.5W		
Consumption (max):	34W		
Voltage:	AC 100-240V		
Stand-by:	0.3W		
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Cable Organization:	Yes		
CONTROLS			
Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
WALL MOUNT			

100 x 100 mm

VESA Compatible: